



SPACE HEATER	
WATTS	440
VOLTS	120/240
PHASE	1

MODEL	5K82111586601M			SERIAL NO.	**		
RATED POWER	700 HP			TYPE	K	ENCLOSURE	WPII
RPM	1190			FRAME	8210S/8211S		
AMP.	92.5/161			LRA(%)	710	CODE	H
VOLTS	4000/2300			SECONDARY AMP.			
PHASE	3	HERTZ	60	SECONDARY VOLTS			
POWER FACTOR	0.86			DRIVE END BRG	ABMA 110BC03J		
EFFICIENCY	94.7 (%)			LUBRICATION	GREASE		
SERVICE FACTOR	1.15			LUBRICANT	SHELL ALVANIA RL3		
INSULATION CLASS	F			OPP.DRIVE END BRG	ABMA 110BC03J		
TEMP.RISE	90 °C	STATOR BY	RTD @ 1.0 SF	LUBRICATION	GREASE		
TEMP.RISE	°C	ROTOR BY	RESISTANCE	LUBRICANT	SHELL ALVANIA RL3		
TIME RATING	CONTINUOUS			OIL PRESSURE	TO		
AMB.TEMP.(°C)	40	MAX	-18 MIN	OIL FLOW	TO	/BRG	
ALTITUDE	3300 ( ft )			MANUFACTURING DATE	****		

**W** LIFTING LUGS ON TOP COVER ARE INTENDED  
**A** FOR LIFTING TOP COVER ONLY. DO NOT USE  
**R** FOR LIFTING ENTIRE MACHINE. LIFTING LUGS ON  
**N** MACHINE FOR LIFTING MACHINE ONLY. DO NOT USE  
**I** FOR LIFTING COUPLED EQUIPMENT AND/OR BASES.  
**G** FAILURE TO OBSERVE THESE PRECAUTIONS MAY  
RESULT IN DAMAGE TO THE EQUIPMENT, INJURY  
TO PERSONNEL, OR BOTH.

MADE IN MEXICO

DRG	REV	000
-----	-----	-----

\*\*TO BE DEFINED

ORIGINAL SHEET SIZE = A3